

## Hydraulic Pump and Accessories, Electric, 5000 PSI

- Develops 5,000 psi of hydraulic pressure
- Easy to operate using manual switch or remote pendant supplied; or optional CT-902RFS foot switch
- Factory set relief valve, pump stops when crimp is complete
- Convenient 120 V operation
- Incorporates Parker type quick-connect fittings to ease installation and save time
- Versatile, can be used with Panduit CT-930LPCH crimp heads



CT-902HP-5K



CT-900LPHPH



CT-902RFS

Part Number	Part Description	Std. Pkg. Qty.
CT-902HP-5K	<p>Hydraulic pump. Develops 5,000 psi output. Pump shuts off when cycle is complete. Will not release until down switch is activated. Compatible with CT-900LPHPH hydraulic hose, CT-930LPCH crimp heads sold separately.*</p> <p>Specifications:                      Pump output: 5000 psi                      Tank capacity: 2.5L incorporates sight gauge for visual inspection of fluid level                      Fluid type: Aero Shell #4 or equal                      Motor: 120 V 50/50Hz                      Current: 6.5 Amps                      Horsepower: 1/2 hp                      Warranty: 1 year</p> <p>Weight: 34 lbs.                      Length: 7"                      Height: 14"                      Width: 6"</p> <p>CT-902HP-5K pump includes:</p> <ul style="list-style-type: none"> <li>• On/off pendant switch on 10' electric cord</li> <li>• Three prong A/C plug on 10' electric cord</li> <li>• Supplied with male Parker type quick-connect fitting assembled to pump</li> </ul>	1
CT-900LPHPH	Electrically non-conductive 10' hose compatible with Panduit CT-902HP-5K hydraulic pump and CT-930LPCH crimp heads, supplied pre-filled with hydraulic fluid for fast start up. Supplied with two female Parker type quick-connect fittings. Warranty: 1 year.	1
CT-902RFS	Dual electrical foot switch that allows convenient "hands free" operation of the Panduit CT-902HP-5K electric hydraulic pumps used with Panduit remote hydraulic crimp heads. Supplied with 10' electric cord that can be directly connected to Panduit hydraulic pumps. Warranty: 1 year.	1

\*For more information on crimp heads, see page E.32.

## Pressure Gauges

- Provide easy visual reading of output force for hydraulic crimping tools
- Easy-to-read crimp force tolerance zone for applicable tools marked on gauge
- Factory calibrated to provide accuracy and quality assurance control of crimping tools in the field
- Blank dies for fixture supplied with test gauge for easy mounting and operation of gauge with crimping tool



PG-1

Part Number	Part Description	Std. Pkg. Qty.
PG-1	In-line pressure gauge provides visual identification of hydraulic output pressure when used with Panduit crimp heads, CT-902HP pump and CT-900HPH hose. Includes steel storage case. Warranty: 90 days.	1
PG-1SC	In-line pressure gauge provides visual identification of hydraulic output pressure when used with Panduit CT-930LPCH crimp heads, CT-902HP-5K pump and CT-900LPHPH hose. Includes steel storage case. Warranty: 90 days.	1