




## Ring Terminal, Nylon Insulated – Funnel Entry

### Type PNF-R

- Ring tongue design assures a secure connection in high vibration applications
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



Part Number	Wire Range	Color Code	Stock Thickness (In.)	Max. Ins. (In.)	Stud Size	Figure Dimensions (In.)			Recommended Installation Tool	Std. Pkg. Qty.**	Std. Ctn. Qty.
						L	W	C			
<b>PNF18-4R-C</b>	22 – 18 AWG	Red	0.03	0.136	#4	0.77	0.25	0.20	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500
<b>PNF18-6RN-C^</b>			0.03	0.136	#6	0.76	0.22	0.18		100	500
<b>PNF18-6R-C^</b>			0.03	0.136	#6	0.77	0.25	0.20		100	500
<b>PNF18-8R-C^</b>			0.03	0.136	#8	0.87	0.31	0.24		100	500
<b>PNF18-10R-C^</b>			0.03	0.136	#10	0.87	0.32	0.25		100	500
<b>PNF18-14R-C^</b>			0.03	0.136	1/4"	1.08	0.46	0.38		100	500
<b>PNF18-56R-C^</b>			0.03	0.136	5/16"	1.08	0.46	0.39		100	500
<b>PNF18-38R-C^</b>			0.03	0.136	3/8"	1.16	0.53	0.41		100	500
<b>PNF14-4R-C^</b>	16 – 14 AWG	Blue	0.03	0.162	#4	0.78	0.25	0.18	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500
<b>PNF14-6RN-C^</b>			0.03	0.162	#6	0.78	0.25	0.18		100	500
<b>PNF14-6R-C^</b>			0.03	0.162	#6	0.87	0.31	0.24		100	500
<b>PNF14-8R-C^</b>			0.03	0.162	#8	0.87	0.31	0.25		100	500
<b>PNF14-10R-C^</b>			0.03	0.162	#10	0.85	0.31	0.29		100	500
<b>PNF14-14R-C^</b>			0.03	0.162	1/4"	1.06	0.46	0.40		100	500
<b>PNF14-56R-C^</b>			0.03	0.162	5/16"	1.06	0.46	0.40		100	500
<b>PNF14-38R-L^</b>			0.03	0.162	3/8"	1.14	0.53	0.45		50	500
<b>PNF10-6R-L^</b>	12 – 10 AWG	Yellow	0.04	0.225	#6	1.06	0.37	0.31	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	50	500
<b>PNF10-8R-L^</b>			0.04	0.225	#8	1.06	0.37	0.31		50	500
<b>PNF10-10R-L^</b>			0.04	0.225	#10	1.06	0.37	0.31		50	500
<b>PNF10-14R-L^</b>			0.04	0.225	1/4"	1.21	0.52	0.38		50	500
<b>PNF10-56R-L^</b>			0.04	0.225	5/16"	1.21	0.52	0.38		50	500
<b>PNF10-38R-L^</b>			0.04	0.225	3/8"	1.29	0.58	0.43		50	500

\*\*Bulk packaging may be available, contact Panduit Customer Service for additional information.

^For military specification cross reference see page D1.96.

‡UL and CSA approved tooling/product combinations. For crimping tool information, see pages D1.83, D1.84, D1.86 and D1.88.

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index