


## Short Circuit Warning Signs

- Aids in compliance with UL 508A requirement



PPS0305W2201Y  
PPS0507W2201Y

### Material Chart

| Material        | Print Method | Temperature Range                  | Features                                                                                                                                                                                                   |
|-----------------|--------------|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Polyester (PPS) | Pre-Printed  | -40°F to 275°F<br>(-40°C to 135°C) | Indoor/outdoor rated; laminated label material protects legend from abrasion and chemicals; resistant to resistant to UV light, chemical atmosphere, and abrasion; excellent life and adhesion properties. |

### Size Reference Chart

| Part Number | Width |        | Height |        | Signs Per Card |
|-------------|-------|--------|--------|--------|----------------|
|             | In.   | mm     | In.    | mm     |                |
| *0305*      | 5.00  | 127.00 | 3.00   | 76.20  | 5              |
| *0507*      | 7.00  | 177.80 | 5.00   | 127.00 | 5              |
| *0710*      | 10.00 | 254.00 | 7.00   | 177.80 | 1              |
| *1014*      | 14.00 | 355.60 | 10.00  | 254.00 | 1              |
| *1209*      | 9.00  | 228.60 | 12.00  | 304.80 | 1              |

\*Denotes the part numbers' prefix and suffix.

## Photoluminescent Safety Signs

- Used to mark egress routes, fire alarms, and fire equipment that is clearly visible for up to ten hours after power is lost
- Absorbs energy from ambient light and releases this energy in the form of a glow when power is lost
- Panduit Photoluminescent Signs meet or exceed the following safety standard specification for photoluminescent safety markings including: ASTM E 2072-00, ASTM E 2073-00, ASTM E 2030-99, DIN67510-1, IMO Resolution A.752.18, ISO/CD 15370, DIN 67510, UL 924, ASTM 162, ASTM 648, ASTM 662, MIL-L-3891 B, NFPA 101 Life Safety Code, OSHA 1910.37



PPS0710G001  
PPS1014G002



PPS0710G020



PPS1209G010



PPS1209G011



PPS1209G012

## Electrical Symbols on Cards

### Material Chart

| Material    | Print Method | Temperature Range                 | Features                                                                                                                                                                                                                                                     |
|-------------|--------------|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Vinyl Cloth | Pre-Printed  | -50°F to 170°F<br>(-46°C to 77°C) | Indoor/outdoor rated; conformable material with repositionable adhesive allows label to be removed and reused or used in temporary applications; provides durability, high temperature resistance, and dimensional stability for rough or textured surfaces. |

| Part Number | Symbol | Description                                             | Marker Size |               | Markers Per Card | Std. Pkg. Card(s) | Std. Ctn. Card(s) |
|-------------|--------|---------------------------------------------------------|-------------|---------------|------------------|-------------------|-------------------|
|             |        |                                                         | In.         | mm            |                  |                   |                   |
| PESC-H-AT   |        | WARNING OF DANGEROUS ELECTRICAL VOLTAGE                 | 0.51 x 0.51 | 13.00 x 13.00 | 68               | 10                | 100               |
| PESC-J-AT   |        |                                                         | 0.75 x 0.75 | 19.00 x 19.00 | 36               | 10                | 100               |
| PESC-H-E    |        | EARTH (GROUND)                                          | 0.51 x 0.51 | 13.00 x 13.00 | 68               | 10                | 200               |
| PESC-J-E    |        |                                                         | 0.75 x 0.75 | 19.00 x 19.00 | 36               | 10                | 100               |
| PESC-H-EC   |        | SAFETY FUNCTION                                         | 0.51 x 0.51 | 13.00 x 13.00 | 68               | 10                | 200               |
| PESC-J-EC   |        |                                                         | 0.75 x 0.75 | 19.00 x 19.00 | 36               | 10                | 100               |
| PESC-H-HT   |        | STATIC SENSITIVE DEVICE – HANDLING PRECAUTIONS REQUIRED | 0.51 x 0.51 | 13.00 x 13.00 | 68               | 10                | 100               |
| PESC-J-HT   |        |                                                         | 0.75 x 0.75 | 19.00 x 19.00 | 36               | 10                | 100               |
| PESC-H-PE   |        | PROTECTIVE CONDUCTOR                                    | 0.51 x 0.51 | 13.00 x 13.00 | 68               | 10                | 100               |
| PESC-J-PE   |        |                                                         | 0.75 x 0.75 | 19.00 x 19.00 | 36               | 10                | 100               |

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index