



High Output T12

TL 85W/HO F72T12/CW/HO ALTO FLUOR. LAMP

Philips T12 fluorescent lamps provide high performance in a wide range of sizes, shapes, and types.

Product data

General Information		Operating and Electrical	
Cap-Base	R17D [R17d (RDC)]	Power (Rated) (Nom)	85 W
Life 3-Hr Start [Hrs]	12000 h	Mechanical and Housing	
Features	ALTO® (ALTO)	Cap-Base Information	Green Base
Footnotes Fluorescent/CFL 1	Approximate initial lumens are for 800 ma. operation. For 1000 ma. operation, lumens are approximately 10% higher and watts approximately 15% higher. (207)	Nominal Length (Inch)	72
Footnotes Fluorescent/CFL 2	Econ-o-watt® lamps are only recommended for use on high power factor lead, indoor ballasts that meet ANSI standards. The lamps are not recommended for use in drafty areas, or locations where the ambient temperature is less than 60°F, except as noted. Also they should not be operated on low power factor ballasts, reduced light or reduced current ballasts, dimming ballasts or emergency system inverter ballasts. (214)	Approval and Application	
Light Technical		Energy Saving Product	Not Applicable
Color Code	33	Mercury (Hg) Content (Nom)	6.8 mg
Luminous Flux (Nom)	6350 lm	Product Data	
Color Designation	Cool White (CW)	Order product name	TL 85W/HO F72T12/CW/HO ALTO FLUOR. LAMP
Design Mean Lumens	5500 lm	EAN/UPC - Product	046677366513
Correlated Color Temperature (Nom)	4100 K	Order code	927893203304
Color Rendering Index (Nom)	62	Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	15
		Material Nr. (12NC)	927893203304
		Net Weight (Piece)	0.001 kg

High Output T12

Dimensional drawing

Product

TL 85W/HO F72T12/CW/HO ALTO FLUOR. LAMP

F72T12 85W/33 HO ALTO

