



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID 71A5752001D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M138-M153				
Lamp Type	250W MH				
Number of Lamps	1 piece/unit				
Circuit Type	SUPER-CWA				
Ballast Type	Magnetic HID				
Base Model	71A5752				
Core Size	4 1/4 x 4 3/4 (2 coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI533-H4				
Ignitor Temperature Rating	105°C				
Capacitor Value	17 MFD				
Capacitor Catalog Number	7C170P40				
Capacitor Requirements	330V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	1.75 in				
Capacitor Height	3.75 in				
Automatic Restart	No				
Operating and Electrical					
Input Voltage	120/208/240/277/480 V				

Input Frequency	60 Hz				
Input Current (Open Circuit)	1.38/0.82/0.7/0.62/0.37 A				
Input Current (Starting)	1.65/0.97/0.84/0.73/0.43 A				
Input Current (Short Circuit)	1.28-1.92/0.75-1.12/0.64-0.97/0.56-0.84/0.32-0.49 A				
Secondary Short Circuit Current	2.35-2.88 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Open Circuit Voltage	280 V				
Input Current (Nom)	2.37/1.39/1.18/1.03/0.6 A A				
Input Power (Nom)	284 W				
Rated Lamp Power	250 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				
Max Ballast-Lamp Distance Remote	2'				
Wiring					


Datasheet, 2016, February 1 data subject to change

Core & Coil (71A) MH 175W - 450W

Recommended Fuse Value	8/5/5/3/2 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	254-308 V				
Approval Marks	ULR CSA certificate EISA RoHS Compliant				
Temperature Marking	A/A/A/A/A				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029A				

Product Data				
Order product name	CORE & COIL HID 71A5752001D			
EAN/UPC - Product	781087123874			
Order code	913701122311			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	1			
Material Nr. (12NC)	913701122311			
Net Weight (Piece)	5.203 kg			

Dimensional drawing



Product	C1	C2	A 1	A2	B1	B2
CORE & COIL HID 71A5752001D	4 in	2.2 in	4.8 in	4.4 in	4.3 in	3.9 in

