



SPECIFICATION SHEET

280-EV6131

EVOLUTION™ DELUXE 6131 CAP STYLE HARD HAT

- Meets ANSI Z89.1-2014 Type I Class E requirements (Class C for Vented)
- Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested
- HDPE strap & webbing clips with polyester webbing straps
- Custom imprinting is available
- High-Density Polyethylene (HDPE) shell
- Suspension can be removed and refitted for reverse wearing
- Slip ratchet size adjustment for true "one size fits all"
- Universal accessory slots
- Vented versions are available to increase air circulation

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating
COLOR	☐ White (-10) ☐ Blue (-50) ☐ Bright Orange (-OR) ☐ Yellow (-20) ☐ Red (-60) ☐ Green (-30) ☐ Lime Yellow (-LY)
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")
EACH WEIGHT	13.2 oz
PACKAGING	10 per case
CASE	9.5" x 23" x 18" / 24.1cm x 58.4cm x 45.7cm
CASE WEIGHT	8.4 lbs / 5.9 kg
COO	USA

BARCODES

ITEM	EACH	DOZEN	CASE
☐ 280-EV6131-10	5038428136631	---	5038428811859
☐ 280-EV6131-20	5038428136648	---	5038428811866
☐ 280-EV6131-30	5038428136655	---	5038428811873
☐ 280-EV6131-50	5038428136662	---	5038428811880
☐ 280-EV6131-60	5038428136679	---	5038428811897
☐ 280-EV6131-LY	5038428136709	---	5038428811927
☐ 280-EV6131-OR	5038428136693	---	5038428811910
VENTED HARD HATS (CLASS C)			
☐ 280-EV6131V-10	5038428136792	---	5038428812016
☐ 280-EV6131V-20	5038428136808	---	5038428812023



DIMENSIONS (in)

	OSFA						
A	11.5						
B	6.375						

