



EtherNet/IP to IEC 60870-5-104 Server Gateway

5201-DFNT-104S

The DFNT-104S modules are the ideal solution for joining EtherNet/IP and IEC60870-5-104 Server networks. The EtherNet/IP gateway is a powerful module designed with both Client and Server support, enabling easy connection to Rockwell Automation PLCs (CLX, SLC, PLC, CPLX, and similar devices). In combination with the IEC 104 Server device support, the module provides a very powerful interface to the many IEC 104 master devices which are in use in the industrial marketplace today. Applications for the module are found in most industries, especially Manufacturing, Oil and Gas, Electrical Power and Food Processing.

How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

EtherNet/IP to IEC 60870-5-104 Server Gateway

5201-DFNT-104S

The ProLinx EtherNet/IP to IEC60870-5-104 Server Gateway creates a powerful connection between an EtherNet/IP network and IEC 104 client devices. This stand-alone DIN-rail mounted protocol gateway provides one Ethernet port.

The Ethernet/IP protocol driver supports the Explicit Messaging implementation of the protocol. User-configurable as both a Client and a Server, the EtherNet/IP port is a very powerful data transfer tool.

The 104S module accepts commands from an attached master unit on the network and generates unsolicited messages.

EtherNet/IP

The EtherNet/IP protocol is one of the primary connectivity tools to the different Rockwell Automation platforms. The Explicit Messaging aspect of the protocol (only) has been implemented in the ProLinx units to provide the data transfer link between the ProLinx units and the Rockwell Automation hardware.

General Protocol Information	
Messaging	PCCC on CIP Explicit Messaging supported
Miscellaneous	125 word read and write data lengths Floating point data supported

EtherNet/IP Server Specifications

In Server mode, the module accepts commands from one or more clients to read/write data stored in the module's internal registers.

EtherNet/IP Server Specifications	
Connections	Five independent TCP server sockets permit remote clients to interact with all data contained in the module.
Data File	Data Table File Start – Fixed at N10 Data Table File Size – 100 or 1000 words
CIP Services Supported	0x4C – CIP Data Table Read 0x4D – CIP Data Table Write

EtherNet/IP Client Specifications

In Client mode, the module controls the read/write data transfer between the gateway and other EtherNet/IP devices. Data transfer can be initiated and executed without any ladder programming being required in the Rockwell Automation hardware.

EtherNet/IP Client Specifications	
General	One client
Command List	Support for 100 commands, each configurable for command, IP address, register to/from addressing and word/bit count.

EtherNet/IP Client Specifications

Polling of command list	User configurable polling of commands, including disabled, continuous and on change of data (write only).
-------------------------	---

IEC 60870-5-104 Server

Operating in the Server mode, the protocol driver accepts commands from an IEC-60870-5-104 Client to read/write data stored in the module's internal registers.

The 104S module acts as an input/output module between the IEC 60870-5-104 Ethernet network and many of the other serial and network protocols, as well as several proprietary interfaces.

General specifications include:

- User-definable module memory usage
- Protocol implementation conforms to the IEC 60870-5-104 specification with fully configurable parameters
- SNTP (Simple Network Time Protocol) timestamping for detailed logging of data transactions.

The 104S module accepts commands from an attached master unit on the network and generates unsolicited messages. These last sets of messages are either spontaneous or cyclic. Data transferred to the host is derived from the module's internal database. The remote master device can control data in the database and hence the devices connected using the other protocol in the module using standard control messages supported in the protocol. The remote master device uses the fully-configured databases in the module to control outputs and monitor inputs.

IEC 60870-5-104 Server

Configurable Parameters	Override StartDT Clear queue on close t1 timeout set value t2 timeout set value t3 timeout set value k (maximum queue) w (latest ack threshold) Time DB Offset
-------------------------	---

General Specifications

The ProLinx Communication Modules provide connectivity for two or more dissimilar network types. The modules, encased in sturdy extruded aluminum, are stand-alone DIN-rail mounted protocol gateways, providing communication between many of the most widely used protocols in industrial automation today.

Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 18 to 36 VDC allowed Positive, Negative, GND Terminals 2.5 mm screwdriver blade
Current Load	500 mA max@ 24 VDC
Operating Temperature	-20 to 50°C (-4 to 122°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)

Specification	Description
Dimensions	Standard: 5.20H x 2.07W x 4.52D in. (13.2cmH x 5.25cmW x 11.48cmD) Extended: 5.20H x 2.73W x 4.52D in. (13.2cmH x 6.934cmW x 11.48cmD)
LED Indicators	Power and Module Status Application Status Serial Port Activity LED Serial Activity and Error LED Status
Configuration Serial Port	DB-9M RS-232 only No hardware handshaking
Ethernet Port (Ethernet modules only)	RJ45 Connector Link and Activity LED indicators
Application Serial Ports	RS-232/422/485 RS-232 handshaking configurable RS-422/485 screw termination included
Serial Port Isolation	2500V RMS port signal isolation per UL 1577 3000V DC min. port to ground and port to logic power isolation
Shipped with Each Unit	Mini-DIN to DB-9M serial cables 4 ft RS-232 configuration cable 2.5mm screwdriver CD (docs and Configuration utility) RS-422/485 DB-9 to Screw Terminal Adaptor (1 or 4, depending on ports)

ProSoft Configuration Builder

ProSoft Configuration Builder (PCB) provides a quick and easy way to manage module configuration files customized to meet your application needs. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations to new projects.

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

To order this product, please use the following:

5201-DFNT-104S	EtherNet/IP to IEC 60870-5-104 Server Gateway
----------------	---

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific

orders@prosoft-technology.com,

fax to +1 661.716.5101

Europe

europa@prosoft-technology.com,

fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.

May 03, 2007