



The same Wallpack as the WP1, but with prismatic glass lens to eliminate yellowing. Lamp supplied.

Color: White

Weight: 7.2 lbs

Project:

Type:

Prepared By:

Date:

Lamp Info

Type: 42W Triple
Watts: 42W
Shape/Size: N/A
Base: N/A
ANSI: N/A
Hours: 12,000
Lamp Lumens: 3200
Efficacy: 70 LPW

Ballast Info

Type: Elec HPF QT
120V: 0.38A
208V: 0.3A
240V: 0.2A
277V: 0.17A
Input Watts: 46W
Efficiency: 91%

Technical Specifications

Listings

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from the ballast.

Construction

Housing:

Die cast aluminum, 1/2" NPS tapped top, both sides and back for conduit or photocontrol. Hinged refractor. Continuous one piece silicone rubber gasket.

Reflector:

Semi-Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

Finish:

Formulated for high-durability and long lasting color.

Conduit Openings:

Top, side and back.

Template:

Drilling template for easy wall box mounting.

Ballast Minimum Starting Temperature:

0°F.

Other


Patents:

Pat. D440,683.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

Precision die cast aluminum housing with durable polyester powder coating

Easy access conduit openings & ballasts for fast internal wiring

Long life lamp included

Silicone gasket remains in place during relamping

Cutoff glare shield for "friendly" lighting

Hinged door swings open and remains captive for easy relamping