



28 thru 42 Watt compact fluorescent Tallpack. Vandal resistant polycarbonate housing. Heavy die-cast aluminum back plate with 1/2" bottom and back conduit opening. Factory installed 120V photocell with bypass cap included. Operating temperature 28w (-20°F), 26, 32 & 42w(0°F). Lamp supplied.

Color: White

Weight: 4.5 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

## Lamp Info

Type: 32w Triple  
Watts: 32W  
Shape/Size: N/A  
Base: N/A  
ANSI: N/A  
Hours: 12,000  
Lamp Lumens: 2400  
Efficacy: 75 LPW

## Ballast Info

Type: Elec HPF QT  
120V: 0.31A  
208V: 0.2A  
240V: 0.2A  
277V: 0.13A  
Input Watts: 32W

## Technical Specifications

### Listings

#### UL Listing:

Suitable for wet locations.

### Construction

#### Reflector:

Die formed aluminum for wide light distribution.  
Moveable Glare Shield for field adjustable light control  
slanted slightly downward for more light on the job.

#### Housing and Refractor:

Vandal resistant polycarbonate molded refractor. Die  
cast aluminum back plate.

#### Ballast Minimum Starting Temperature:

0°F.

### Electrical

#### Ballast Housing:

Stamped steel painted white.

#### Other

#### Back Plate:

Heavy die cast aluminum. 1/2" bottom conduit  
knockout. Knockouts for mounting to 3" or 4" junction  
boxes.

#### Patents:

The unique RAB Tallpack is protected by U.S. Patent  
D569,029; China Patent ZL200730149211.2; Taiwan  
Patent D124,864 and Canada Patent D121,993.

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB  
may be able to manufacture this product to be  
compliant with the Buy American Act (BAA). Please  
contact customer service to request a quote for the  
product to be made BAA compliant.

## Features

- Heavy, die cast aluminum back plate with box mounting template
- Shades work great with tallpacks!
- 1/2" bottom conduit knockout
- Packaging has product features, ballast and lamp specifications
- Lighting layout photometrics and installation instructions are available