



Motion activated task light. 21" long, 13 Watt fixture with integrated 180 $^\circ$ view sensor that swivels 330 $^\circ$. Sensor can control up to 250 Watts fluorescent. Lamps supplied.

Color: White Weight: 1.7 lbs

Project:	Туре:
Prepared By:	Date:

Lamp Info		Ballast Info	
Type:	T5	Type:	NPF 120V
Watts:	13W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	7,500	Input Watts:	0W
Lamp Lumens:	870		
Efficacy:	N/A		

Technical Specifications

Listings

UL Listing:

For indoor applications.

Construction

Compatibility:

Compatible with most electronic ballasts. Not compatible with instant start ballasts.

Vandal Resistant Lens:

Hard lens resists vandalism.

Fixture Housing:

Formed sheet metal with translucent styrene lens.

Fixture Finish:

Bright white epoxy powder coating.

Fixture Sockets:

Miniature bi-pin, G5.

Electrical

Voltage:

120 volts AC, 60 Hz.

Wall Switch Manual Override:

Two flip logic prevents activation by momentary power outages. Override resets to auto at dawn. No extra wiring needed.

Switching Capacity:

500 watts Incandescent or 250 watts Fluorescent.

Sensor Characteristics

Time Adjustment:

Adjustable from 5 seconds to 15 minutes.

Sensor Construction:

Precision molded Lexan.

Sensor Wires:

12" long.

Detection:

180° degree view.

Other

Detection Zone:

120° by 30', aimable.


Lamps Supplied:

T5.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

Motion activated Undercabinet light

120° by 30' view sensor swivels 330° to aim as needed

High quality 1" thin undercabinet fixture in a variety of lengths

Retrofit sensor fits in standard undercabinet fixture switch knockouts

Adapts existing undercabinet task lights to sensor control

Easy 3-wire installation

Controls up to 250 Watts Fluorescent

Time adjustable from 5 seconds to 15 minutes