



Mid sized wallpack. All aluminum precision die cast construction with tempered glass refractor. Lamp supplied.

Color: White

Weight: 16.4 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

## Lamp Info

Type: 42W Triple  
Watts: 42W  
Shape/Size: N/A  
Base: N/A  
ANSI: N/A  
Hours: 10,000  
Lamp Lumens: 3200  
Efficacy: 70 LPW

## Ballast Info

Type: Elec HPF QT  
120V: 0.38A  
208V: N/A  
240V: N/A  
277V: N/A  
Input Watts: 46W  
Efficiency: 91%

## Technical Specifications

### Electrical

#### Photocell:

120V Button Photocell Included. Photocell is only compatible with 120V.

### Listings

#### UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

### Construction

#### Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

#### Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

#### Cutoff Lens:

Tempered glass.

#### Finish:

Formulated for high-durability and long lasting color.

#### Weight:

16.35.

#### Ballast Minimum Starting Temperature:

0°F.

### Optical

#### Refractor:


Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

### Other

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- Precision die cast aluminum housing with durable polyester powder coating
- Tempered Glass Refractor
- Drilling template for easy box mounting
- Silicone gasket remains in place during relamping
- Top, side and back conduit openings
- Long life lamp included