# WP2F42W/E1/PC





Mid sized wallpack with emergency battery Backup and glass lens. All aluminum precision die cast construction with tempered glass refractor.

Color: White

Weight: 8.3 lbs

Project:	Туре:
Prepared By:	Date:

Lamp Info		Ballast Info	
Type:	42W Triple	Type:	Elec HPF QT
Watts:	42W	120V:	0.38A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	10,000	Input Watts:	46W
Lamp Lumens:	3200	Efficiency:	91%
Efficacy:	70 LPW		

## **Technical Specifications**

#### **Electrical**

#### **Emergency Battery Backup:**

Bodine "Coldpak" will operate the CFL lamp for 90 minutes if power fails. Rated -20°C to 55°C. Battery is a maintenance free NiCad with 7 - 10 year life. Wired for 120V.

#### Photocell:

120V Button Photocell Included. Photocell is only compatible with 120V.

### Listings

## **UL Listing:**

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

### Construction

#### Housing:

Die cast aluminum, 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame. Continuous silicone rubber gasket.

#### Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

#### **Cutoff Lens:**

Tempered glass.

## Finish:

Formulated for high-durability and long lasting color.

### Optical


#### Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

#### Other

## Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.



## **Features**

Emergency battery backup meets NEC requirement

Test button for required maintenance checks

Indicator light illuminates when charging

Maintenance free NiCad battery has 7-10 year life

Hinged door frame opens and remains captive for easy relamping

Top, side and back conduit openings

Long life lamp included