

New Integra Hood for Friendly Lighting. Awesome performance with quality and value from this compact 400 and 250 Watt HID flood.

Color: Bronze Weight: 30.0 lbs

Project:	Туре:
Prepared By:	Date:

/			
Lamp Info		Ballast Info)
Туре	T15	Type	CWA-HPF QT
Watts	200W	120V	1.4/2.0A
Shape/Size	N/A	208V	.8/1.2A
Base	N/A	240V	.7/1.0A
ANSI	N/A	277V	.6/.9A
Hours	15,000	Input Watts	232W
Lamp Lumens	21,000	Efficiency	86%
Efficacy	90.5 LPW		

Technical Specifications

Listings

UL Listing:

Suitable for wet locations. Suitable for ground mounting.

Construction

Housing:

Precision die cast aluminum

Reflector:

High quality anodized aluminum

Lens:

Tempered shock resistant glass

Lens Gasket:

Molded one-piece silicone in die cast retaining groove to remain in place during relamping

Finish:

Formulated for high durability and long-lasting color

EPA:

1.3.

Electrical

Socket:

Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

Other

Patents:

Pat. D547,478.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions 125/8" 32 cm 133/4" 34.9 cm 23 cm

Features

Optional glare hood, wire guard or polycarbonate shield

Reflector designed for precise beam control

Stainless steel screws included

Long life lamp included

Supplied with 3' of STW cord

Rugged trunnion or slipfitter mounting

New 2" Integra hood to reduce light trespass and glare