



15" round die cast aluminum housing with vandalproof refractor for optimum parking garage light distribution. 150 or 175 w vertical mount Metal Halide or 100,000 hour Induction. Lamp supplied.

Color: Bronze

Weight: 21.0 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

#### Lamp Info

Type	ED17
Watts	150W
Shape/Size	N/A
Base	N/A
ANSI	N/A
Hours	24,000
Lamp Lumens	16,000
Efficacy	85.1 LPW

#### Ballast Info

Type	HX-HPF QT
120V	2/1.7A
208V	1.2/1.0A
240V	1/.9A
277V	.9/.8A
Input Watts	188W
Efficiency	80%

## Technical Specifications

### Listings

#### UL Listing:

Suitable for wet locations. Covered Ceiling Mount Only. Fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

### Construction

#### Mounting:

Ceiling mount only. Not suitable for pendant mounting.

#### Housing:

Cast aluminum housing with 1/2 inch threaded NPS conduit access on 2 sides at 180° and the top of the housing

#### Housings:

Die cast aluminum with powder coat bronze or white finish

#### Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER).

#### Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

#### Fluorescent Ballast Starting Temperatures:

Electronic QT 0°F/-18°C NPF 120V 32°F / 0°C

### Electrical

#### Sockets:

HPS & MH Medium base 4kv Pulse Rated Glazed porcelain CFL Plug-in type, thermoplastic

#### HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure.

#### Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts

### Optical

#### Refractor:

Injection molded polycarbonate, designed for maximum structural strength

### Other

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions

dimension

## Features

Vertical lamp for better light disbursement and heat dissipation

Both Vandal proof Center Pin Torx and slotted Phillips head screws supplied

Tough polycarbonate refractors and Die cast aluminum housings

Philips QL induction system with 100,000-hours available. Consult factory