

New Integra Hood for Friendly Lighting. Awesome performance with quality and value from this compact 400 and 250 Watt HID flood.

Color: Bronze Weight: 31.0 lbs

Project:	Туре:
Prepared By:	Date:

Lamp Info			Ballast Info		
	Туре	ED28	Туре	CWA-HPF QT	
	Watts	250W	120V	1.4/2.5A	
	Shape/Size	N/A	208V	.8/1.5A	
	Base	N/A	240V	.7/1.3A	
	ANSI	N/A	277V	.6/1.1A	
	Hours	15,000	Input Watts	288W	
	Lamp Lumens	25,000	Efficiency	87%	
	Efficacy	86.8 LPW			
	-				

# **Technical Specifications**

# Listings

# **UL Listing:**

Suitable for wet locations. Suitable for ground mounting.

# Construction

# Housing:

Precision die cast aluminum

# Reflector:

High quality anodized aluminum

# Lens:

Tempered shock resistant glass

# Lens Gasket:

Molded one-piece silicone in die cast retaining groove to remain in place during relamping

### Finish:

Formulated for high durability and long-lasting color

# EPA:

1.3.

# **Electrical**

# Socket:

Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts

# **Pulse Start:**

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

# Other

# Patents:

Pat. D547,478.

# **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

# Dimensions 12<sup>5</sup>/<sub>8"</sub> 32 cm 13<sup>3</sup>/<sub>4"</sub> 34.9 cm 23 cm 23 cm Fits 2 3/8" 6cm (OD) Tenon

# **Features**

Optional glare hood, wire guard or polycarbonate shield

Reflector designed for precise beam control

Stainless steel screws included

Long life lamp included

Supplied with 3' of STW cord

Rugged trunnion or slipfitter mounting

New 2" Integra hood to reduce light trespass and glare