



Color: Bronze

Weight: 25.1 lbs

Project:	Type:
Prepared By:	Date:

Lamp Info		Ballast Info	
Type	ED28	Type	CWA-HPF QT
Watts	250W	120V	1.4/2.5A
Shape/Size	N/A	208V	.8/1.2A
Base	N/A	240V	.7/1.0A
ANSI	N/A	277V	.6/1.1A
Hours	15,000	Input Watts	288W
Lamp Lumens	25,000	Efficiency	87%
Efficacy	86.8 LPW		

Technical Specifications

Listings

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from the ballast.

Construction

Housing:

Die cast aluminum 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame, Continuous silicone rubber gasket.

Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

Finish:

Formulated for high durability and long-lasting color

Electrical

Pulse Start:


Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- Hinged door frame opens and remains captive for easy relamping
- Precision die cast aluminum housing with durable polyester powder coating
- Drilling template for easy box mounting
- Silicone gasket remains in place during relamping
- Tempered glass refractor
- Long life lamp included