

Туре:
Date:

LED Info Driver Info Watts 25.00W Input Voltage Ballast Dependent 4000K (Cool Power Factor Ballast Dependent Color Temp White) Flicker N/A Lumens 3,500 THDi N/A Efficacy 140 LPW

Technical Specifications

Technical Specifications

Product Type:

Linear

Bulb Shape:

T5

Nominal Length:

rtommar Longui.

4FT

Finish: Frosted

Wattage:

wattage.

25W Wattage Equivalency:

54W Fluorescent

Typical Lumen Output:

3500

Efficacy:

140 lm/W

Color Temperature:

4000K Cool White

CRI: 82

Base Type:

__

G5

L70 Lifespan:

50,000 hours

Operating Temperature:

-20°C - 45°C

Dimmable:

No

Beam Angle:

240°

Color Accuracy 82 CRI L70 Accuracy 50,000

Warranty:

5-Year, No-Compromise Warranty

Installation Type:

Type A, Plug and Play

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Power Factor:

Technical Specifications (continued)

Electrical Characteristics Input Current @ 120V: Listings

Input Voltage: Ballast Dependent UL Listed:


Ballast Dependent Input Current @ 277V: Yes

Ballast Dependent THDi: PZBY9608

Ballast Dependent

Operating Frequency: <20% CEC Status:

Ballast Dependent Lawful for sale in California



Features

FLUORESCENT REPLACEMENT - Replace conventional fluorescent T8 linear tubes

DLC Product Code:

EASY TO INSTALL - Simply plug and play No rewiring, no tools, no instructions

50,000-HOUR LIFESPAN - Lasts 1.6x longer than conventional fluorescent tubes

ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures

DIFFUSION COATING - Will maintain the same light quality over time and won't yellow, shrink, or wrinkle

BALLAST COMPATIBLE - Please check Compatibility List

SAVE ENERGY AND MONEY - Approximately 40% more efficient than conventional T8 lamps

INSTANT ON - No warmup time required, full brightness instantly

MERCURY FREE - Environmentally friendly vs fluorescent technologies