



Mini Sensor and 75w or double 75w quartz bullet floods. Quartz Bullet has silicone O-ring gasket, thick tempered glass lens, internal and external cooling fins. Gold plated socket contacts and 250°C Teflon coated wires for extended lamp life. Lamp supplied.

Color: White

Weight: 2.9 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

## Technical Specifications

### Listings

#### UL Listing:

Suitable for wet locations

### Optical

#### Lamp:

(2) 75W T4 Bipin Lamp included

### Electrical

#### Socket:

GY8

#### Switching Capacity:

500 watts Incandescent or 100 watts Fluorescent at 120 volts

#### Voltage:

120 volts AC, 60Hz

#### Surge Protection:

Withstands up to 3000 volts

#### Manually Override:

Double flip wall switch logic prevents activation by short power outages. Resets after 6 hours. No extra wiring needed.

### RF Immunity:

Circuits fully shielded for maximum radio frequency immunity

### Sensor Characteristics

#### Detection Zone:

Full 180 degrees by 30'

#### Quick Test Time:

5 seconds test time for fast installation. Works day or night.

#### "No Hands" Auto Testing:

Auto mode starts after 4 minutes of testing. No adjustment needed.

#### Time Adjustment:

5 seconds to 15 minutes

#### Photoelectric Control:

Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications.

### Construction

#### Vandal Resistant Lens:

Hard lens resists vandalism

### Case Construction:

Precision molded Lexan

### Built for Severe Conditions:

Double weatherproofing for long life

### LED Characteristics

#### LED Detection Indicator:

Glowes red day and night for "on-guard" deterrence

### Other


### Patents:

RAB sensor fixture designs are protected under U.S. and international intellectual property laws.

### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- Surge protected
- 180° detection pattern
- Quick installation with 5 second test time and auto test logic
- LED "on guard" indicator
- Protected manual override with auto reset after 8 hours or at dawn