



The eight-foot SHARK is available in 70W and 100W versions. This impact-resistant linear LED washdown fixture is ideal for tunnels, stairwells and other hard-to-reach areas where relamping is difficult and costly.

Color: White

Weight: 25.7 lbs

Project:

Type:

Prepared By:

Date:

## Driver Info

Type	Constant Current	Watts	70.00W
120V	0.62A	Color Temp	3000K (Warm)
208V	0.38A	Color Accuracy	75 CRI
240V	0.33A	L70 Lifespan	100,000
277V	0.28A	Lumens	10,072
Input Watts 74.40W		Efficacy	135.4 LPW
Efficiency 94%			

## LED Info

## Technical Specifications

### Listings

#### UL Listing:

Suitable for wet locations

#### NSF:

NSF Certified by Public Health and Safety

#### ABS:

Approved for use on mobile offshore drilling units and shipping vessels

#### NEMA Rating:

4X, protected against corrosion

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

#### DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. DLC Product Code: P2CDYAZE

### Electrical

#### Driver:

Class 2 Constant Current, 4kV, 100-277VAC, 50-60Hz, 120V: 0.62A, 208V: 0.38A, 240V: 0.33A, 277V: 0.28A

#### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims as low as 10%.

#### THD:

7.5% at 120V, 8.9% at 277V

#### Power Factor:

99.2% at 120V, 95.9% at 277V

#### Surge Protection:

4kV

### Construction

#### IP Rating:

Ingress Protection rating of IP66 for dust and water

#### Housing:

5VA impact-resistant polycarbonate. 1/2" openings for conduit and bushing/cord entry. Polycarbonate is affected by cleaning agents or other liquids containing partial solvents such as low molecular weight aldehydes and ethers, ketones, esters, aromatic hydrocarbons and perchlorinated hydrocarbons. [Click here for a detailed list of damaging chemicals.](#)

#### Mounting:

Quick-mount, surface, stainless steel spring clips supplied. 4 additional mounting accessory kits available.

#### Lens:

Diffuse polycarbonate lens for low glare and maximum protection

#### Gaskets:

EVA silicone foam

#### Maximum Ambient Temperature:

Suitable for use in 40°C (104°F)

#### Cold Weather Starting:

The minimum starting temperature is -30°C (-22°F)

#### Installation:

6ft 5-wire cord installed on fixture for easy installation on SHARK8. Tether Cables are provided for easy installation. Quick connector may be used for quick and easy wiring.

## Technical Specifications (continued)

## Construction

## Green Technology:

Mercury and UV free. RoHS-compliant components.

## Finish:

Formulated for high durability and long-lasting color

## LED Characteristics

## LEDs:

Long-life, high-efficacy surface mount LEDs

## Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

## Color Stability:

LED color temperature is warranted to shift no more than 200K in CCT over a 5-year period

## Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

## Other


## Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

NSF certified for use in food-preparation facilities

American Bureau of Shipping (ABS) approved

Ideal for tunnels and stairwells

Mounting options:

Chain, junction box, angled surface mount, ceiling mount or vandal-resistant surface mount

IP66 AND NEMA 4X ratings protect against dust, water ingress & corrosion

5-Year, No-Compromise Warranty

100,000-Hour LED lifespan

## Ordering Matrix

Family	Length	UL Listing	Wattage	Color Temp	Finish	Driver Options	Options
SHARK	8		70	Y	W	/D10	
2 = 2 ft.	Blank = Standard		18 = 18W (2 ft.)	Blank = 5000K (Cool)	W = White	/D10 = 0-10V Dimming, 120-277V	Blank = No Option
4 = 4 ft	M = Marine Listed		25 = 25W (2 ft.)	N = 4000K (Neutral)		/480 = On/Off, 480V	/E2 = Emergency Battery Backup
8 = 8 ft			36 = 36W (4 ft.)	YN = 3500K (Warm Neutral)		/480/D10 = 0-10V Dimming, 480V	/LC = Lightcloud® Controller, 120-277V
			50 = 50W (4 ft.)	Y = 3000K (Warm)			/BL = Bi-Level Dimming, 120-277V
			70 = 70W (8 ft.)	ft.)			/MVS = Microwave Motion Sensor, 120-277V
			100 = 100W (8 ft.)				