

8911DPSO22V02

STARTER 600VAC 25AMP DPS +OPTIONS

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 296.00 USD

Main

Commercial Status	Commercialised
Product or component type	Definite Purpose Starter
Line Rated Current	25 A
Motor power hp	7.5 hp 575 V 7.5 hp 460 V 7.5 hp 230 V 1.5 hp 115 V AC 1 phase 3 hp 230 V AC 1 phase
System Voltage	600 V AC
Control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase

Complementary

NEMA degree of protection	Not rated (open device)
Locked rotor rated current	100 A 575 V AC 125 A 460 V AC 150 A 230 V AC
Poles description	2P
Range of product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	1

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901342779
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	CN

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------