Product data sheet Characteristics

8911DPSO42V02 STARTER 600VAC 40AMP DPS +OPTIONS

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 365.00 USD

Main	
Commercial Status	Commercialised
Product or component type	Definite Purpose Starter
Line Rated Current	40 A
Motor power hp	7.5 hp 230 V AC 1 phase

3 hp 115 V AC 1 phase
System Voltage 600 V AC

Control circuit voltage 120 V AC 60 Hz 110 V AC 50 Hz

Phase 1 phase

Complementary

NEMA degree of protection	Not rated (open device)	
Locked rotor rated current	160 A 575 V AC 200 A 460 V AC 240 A 230 V AC	
Poles description	2P	
Range of product	DPS	
Thermal overload type	Melting alloy	
Number of thermal units required	1	;

Ordering and shipping details

Category	21381 - 8911 DP	
Discount Schedule	CP1	
GTIN	00785901744610	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	CN	

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will not be Compliant	_
REACh	Reference not containing SVHC above the threshold	

Contractual warranty

on a detail in an an ag		
Warranty period	18 months	