

Product data sheet

Characteristics

171CCC98030

M1/M1E processor adaptor - 1 Ethernet, 1 Modbus - 50 MHz

Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	End of commercialisation
Range of product	Modicon Momentum automation platform
Product or component type	M1/M1E processor adaptor
Concept	Transparent Ready
Level or class	Class B10
Software designation	ProWORX 32 ProWORX NxT V2.0 Modsoft >= V2.5 Concept V2.6
Communication port protocol	Ethernet Modbus
Processor name	X 86 based (INTEL, AMD) IEC executive
Clock frequency	50 MHz

Complementary

Web services	Data editor Rack viewer Web page loader Web page loader software tool
Ethernet service	I/O scanning Modbus TCP messaging
Discrete I/O processor capacity	8192 I/8192 O
Memory type	RAM 544 kB Flash 1 MB
Memory description	Data 24 kB Program memory 200 kB IEC Program memory 18 kB LL984
Material	Lexan
Word length	16 bit
[Us] rated supply voltage	5.0 V DC +/-5 %
Supply	By Momentum I/O base
Exact time for 1 K instruction	1 ms
Register I/O processor capacity	26048 I/26048 O
I/O limit processor capacity	I/O local on Modbus
Number of port	1 Ethernet 1 RS485
Marking	CE
Product weight	0.09 lb(US) (0.042 kg)

Environment

Protective treatment	TC
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	5...96 % without condensation
Operating altitude	6561.68 ft (2000 m)
Shock resistance	<= 15 gn peak (duration = 11 ms) half sine wave acceleration

Vibration resistance	0.75 mm d.a 1 gn
Product certifications	CUL FM Class 1 Division 2 Nema type 250 UL

Ordering and shipping details

Category	18206 - MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	00785901396383
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1047 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------