Product data sheet Characteristics

H364AWKEI SW FUSIBLE HD 200A 3P NEMA12/INTERLOCK



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2906.00 USD

			٠	
N	/	2	П	r

Commercial Status	Commercialised
Disconnector device type	Fusible disconnect switch
Enclosure type	Dustproof enclosure for indoor/outdoor lce/Sleet proof enclosure for indoor/outdoor Rainproof enclosure for indoor/outdoor
Series name	Heavy duty

Complementary

[In] rated current	200 A	
AWG gauge	AWG 6250 kcmil for aluminium/copper cable	
Device mounting	Surface	
Electrical connection	Lugs	
Enclosure material	Galvannealed steel	
Number of poles	3	
Permissible voltage	<= 600 V	
Short circuit protection	10 kA for H or K fuse 200 kA for R or J fuse	
Switch function	TPST	
Wiring configuration	Without neutral	

Environment

Product certifications	UL listed	
Contacts type and composition	1 NO/1 NC	
NEMA degree of protection	NFMA 3R/12	

Ordering and shipping details

Category	00160 - DE1 MISC	
Discount Schedule	DE1	
GTIN	00785901753964	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	US	

Offer Sustainability

Sustainable offer status	ainable offer status Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	of life instructions Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	