



Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	End of commercialisation
Product or component type	Load Centre
Range of product	Homeline
Load centre type	Main lugs
Line Rated Current	125 A
Number of spaces	30
Short-circuit current	10 kA
Number of circuits	30
Number of tandem circuit breakers	0
Phase	1 phase
System Voltage	120/240 V AC

Complementary

AWG gauge	AWG 6...AWG 2/0 (copper) AWG 6...AWG 2/0 (aluminium)
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover finish	Gray baked enamel
Box number	10
Product certifications	UL listed file:E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901457695
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1248 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	Lifetime
-----------------	----------