



Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	End of commercialisation
Range of product	8501K
Product or component type	Relay
Contacts material	Silver tin oxide
Switch function	DPDT
Control circuit voltage	120 V AC
Rated power in hp	0.5 hp 240 V 0.33 hp 120 V
Maximum switching voltage	240 V AC
Mounting support	Socket
Ambient air temperature for operation	-40...131 °F
Shape of pin	Spade
Product certifications	CE CSA RoHS UL recognized
Operating time	8 ms drop-out 8 ms pick-up
Local signalling	No indicator
Control type	Without
Product compatibility	8501NR82
Relay type	General purpose

Ordering and shipping details

Category	21144 - 8501 KU
Discount Schedule	CP2
GTIN	00785901480853
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	N
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental Profile
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------