Product data sheet Characteristics

8911DPSO53V14 STARTER 600VAC 50AMP DPS +OPTIONS

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 638.00 USD

Main	
Commercial Status	Commercialised
Product or component type	Definite Purpose Starter
Line Rated Current	50 A
Motor power hp	30 hp 575 V AC 3 phases 30 hp 460 V AC 3 phases 15 hp 230 V AC 3 phases 10 hp 230 V AC 1 phase 3 hp 115 V AC 1 phase
System Voltage	600 V AC
Control circuit voltage	24 V AC 50/60 Hz
Phase	3 phases

Complementary

NEMA degree of protection	Not rated (open device)	
Locked rotor rated current	200 A 575 V AC 250 A 460 V AC	
Poles description	300 A 230 V AC 3P	
Range of product	DPS	
Thermal overload type	Melting alloy	
Number of thermal units required	3	

Ordering and shipping details

21381 - 8911 DP	
CP1	
00785901179818	
1	
Non-Stock - Not normally stocked in distribution facility	
N	
CN	
	CP1 00785901179818 1 Non-Stock - Not normally stocked in distribution facility N

Offer Sustainability

Sustainable offer status	Not Green Premium product	_
RoHS (date code: YYWW)	Will not be Compliant	_
REACh	Reference not containing SVHC above the threshold	_

Contractual warranty

Warranty period	18 months