

Product availability: Stock - Normally stocked in distribution facility

Price\*: 12578.00 USD



### Main

|                           |                    |
|---------------------------|--------------------|
| Commercial Status         | Commercialised     |
| Range                     | PratiKa            |
| Product or component type | Interlocked socket |
| Device short name         | PratiKa socket     |
| Plug, socket category     | Low voltage        |
| Poles description         | 3P + N + E         |
| Network type              | AC                 |
| Outlet standard           | Industrial         |

### Complementary

|                                |   |
|--------------------------------|---|
| Line Rated Current             | 125 A   |
| [Ue] rated operational voltage | 380...415 V   |
| Network frequency              | 50/60 Hz  |
| Protection type                | Residual current breaker with overcurrent protection (RCBO) |
| Plug, socket material          | Self-extinguishing engineering polymer housing :            |
| Connections - terminals        | Captive screws  |
| Cable cross section            | <= 0.15 in <sup>2</sup> (95 mm <sup>2</sup> )               |
| Cable entry                    | Cable gland   |
| Thread type                    | Pg 42   |
| Product weight                 | 25.57 lb(US) (11.6 kg)                                      |
| Height                         | 27.95 in (710 mm)   |
| Width                          | 10.63 in (270 mm)   |
| Depth                          | 8.46 in (215 mm)  |
| Colour                         | Grey ( RAL 7035 )   |
| Voltage colour                 | Red   |

### Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN 60309-1<br>EN 60309-2  |
| IP degree of protection               | IP65 conforming to IEC 60529  |
| IK degree of protection               | IK08 conforming to EN 62262   |
| Fire resistance                       | 1760 °F (960 °C) conforming to IEC 60695-2-11                               |
| Relative humidity                     | 90 % ( 68 °F (20 °C) )<br>70 % ( 86 °F (30 °C) )<br>50 % ( 104 °F (40 °C) ) |
| Ambient air temperature for operation | 95 °F (35 °C) ( 86400 s )   |

Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 00033 - DT SWITCH,NEMA1                           |
| Discount Schedule     | DE1   |
| GTIN                  | 00785901631613                                    |
| Nbr. of units in pkg. | 1   |
| Product availability  | Stock - Normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | US  |

Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|