Product data sheet Characteristics

HOM30M150C LOAD CENTRE HOM MB 240V 150A 1PH 30SP



Product availability: Stock - Normally stocked in distribution facility

Price*: 776.00 USD

Main	
Commercial Status	Commercialised
Product or component type	Load Centre
Range of product	Homeline
Load centre type	Main breaker
Line Rated Current	150 A
Number of spaces	30
Short-circuit current	22 kA

Number of circuits 30

Number of tandem 0

circuit breakers

Phase 1 phase
System Voltage 120/240 V AC

Complementary

Complementary	
AWG gauge	AWG 4250 kcmil (copper) AWG 4250 kcmil (aluminium)
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover finish	Gray baked enamel
Box number	10
Product certifications	UL listed file:E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1	
Discount Schedule	DE3C	
GTIN	00785901061373	
Nbr. of units in pkg.	1	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1411 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	Lifetime