Product data sheet
Characteristics

8538SCA24V02G26P1S
COMBO STARTER 600VAC 27A NEMA

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2120.00 USD

Main

Commercial Status	Commercialised
Product or component type	Combination Starter
Range of product	S
Control circuit	Separate control circuit
Control type	No control units
NEMA degree of protection	NEMA 12/3R painted sheet steel with external reset
Auxiliary contact composition	Without
Motor power hp	10 hp 575 V AC 3 phases 10 hp 460 V AC 3 phases
Poles description	3P
System Voltage	600 V AC
NEMA size	1
Control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Local signalling	Red indicator on incandescent
Motor starter type	Non reversing
Thermal overload type	Melting alloy
Number of thermal units required	3
Disconnector device type	Fusible disconnect switch H 30 A

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative