

Product data sheet

Characteristics

RE7CP13BU

adjustable symmetrical flashing relay - 0.05..1 s -
24 V AC DC - 2OC

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

| | |
|-------------------------------|--------------------------|
| Commercial Status | End of commercialisation |
| Range of product | Zelio Time |
| Product or component type | Industrial timing relay |
| Contacts type and composition | 2 C/O |
| Component name | RE7 |
| Time delay type | D |
| Time delay range | 0.05 s...300 h |

Complementary

| | |
|---|---|
| Discrete output type | Relay |
| Contacts material | 90/10 silver nickel contacts |
| Width pitch dimension | 0.89 in (22.5 mm) |
| [Us] rated supply voltage | 42...48 V AC/DCat 50/60 Hz 24 V AC/DC at 50/60 Hz 110...240 V ACat 50/60 Hz |
| Voltage range | 0.85...1.1 Us |
| Connections - terminals | Screw terminals, clamping capacity: 2 x 2.5 mm ² flexible without cable end Screw terminals, clamping capacity: 2 x 1.5 mm ² flexible with cable end |
| Tightening torque | 5.31...9.73 lbf.in (0.6...1.1 N.m) |
| Setting accuracy of time delay | +/- 10 % of full scale |
| Repeat accuracy | +/- 0.2 % |
| Temperature drift | < 0.07 %/°C |
| Voltage drift | < 0.2 %/V |
| Minimum pulse duration | 20 ms |
| Reset time | 50 ms |
| Maximum switching voltage | 250 V AC/DC |
| Mechanical durability | 20000000 cycles |
| [Ith] conventional free air thermal current | 8 A |
| [Ie] rated operational current | <= 3 A AC-15at 158 °F (70 °C) conforming to IEC 60947-5-1/1991/VDE 0660 <= 0.2 A DC-13 115 Vat 158 °F (70 °C) conforming to IEC 60947-5-1/1991/VDE 0660 <= 0.1 A DC-13 250 Vat 158 °F (70 °C) conforming to IEC 60947-5-1/1991/VDE 0660 <= 2 A DC-13 24 Vat 158 °F (70 °C) conforming to IEC 60947-5-1/1991/VDE 0660 |
| Minimum switching capacity | 12 V / 10 mA |
| Potentiometer characteristic | Linear 47 kOhm (+/- 20 %), 0.2 W, cable length: <= 82.02 ft (25 m) Z1Z2terminal(s) |
| Marking | CE |
| Overvoltage category | III conforming to IEC 60664-1 |
| [Ui] rated insulation voltage | 300 V between contact circuit and power supply CSA certified 300 V between contact circuit and control inputs CSA certified 250 V between contact circuit and power supply IEC certified 250 V between contact circuit and control inputs IEC certified |
| Supply disconnection value | > 0.1 Uc |
| Operating position | Any position without derating |
| Surge withstand | 2 kV conforming to IEC 61000-4-5 level 3 |

| | |
|-------------------------|--|
| Power consumption in VA | 2.8 VA 110 V 12.5 VA 240 V 1.2 VA 24 V 2 VA 48 V |
| Power consumption in W | 1.6 W 48 V 0.8 W 24 V |
| Terminal description | (15-16-18)OC_ON (25-26-28)OC_ON (B1-A2)CO (Z1)UNUSED (Z2)UNUSED ALT |
| Height | 3.07 in (78 mm) |
| Width | 0.89 in (22.5 mm) |
| Depth | 3.15 in (80 mm) |
| Product weight | 0.33 lb(US) (0.15 kg) |

Environment

| | |
|---------------------------------------|--|
| Immunity to microbreaks | 3 ms |
| Standards | EN/IEC 61812-1 |
| Product certifications | CSA GL UL |
| Ambient air temperature for storage | -40...185 °F (-40...85 °C) |
| Ambient air temperature for operation | -4...140 °F (-20...60 °C) |
| Relative humidity | 15...85 % (3K3) conforming to IEC 60721-3-3 |
| Vibration resistance | 0.35 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 15 gn 11 ms conforming to IEC 60068-2-27 |
| IP degree of protection | IP50 (housing) IP20 (terminals) |
| Pollution degree | 3 conforming to IEC 60664-1 |
| Dielectric strength | 2.5 kV |
| Non-dissipating shock wave | 4.8 kV |
| Resistance to electrostatic discharge | 8 kV (in air) conforming to IEC 61000-4-2 level 3 6 kV (in contact) conforming to IEC 61000-4-2 level 3 |
| Resistance to electromagnetic fields | 9.14 V/yd (10 V/m) conforming to IEC 61000-4-3 level 3 |
| Resistance to fast transients | 2 kV conforming to IEC 61000-4-4 level 3 |
| Disturbance radiated/conducted | CISPR 11 group 1 - class A CISPR 22 - class A |


Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22376 - RELAYS-MEASUREMENT(RM4) |
| Discount Schedule | CP2 |
| GTIN | 00785901979203 |
| Nbr. of units in pkg. | 1 |
| Product availability | Non-Stock - Not normally stocked in distribution facility |
| Returnability | N |
| Country of origin | ID |


Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|


Rail Mounting



Screw Fixing




Internal Wiring Diagram



Recommended Application Wiring Diagram

Start on Energisation




- 1 Supply
- 2 12...48 V
- 3 24 V

Performance Curves

A.C. Load Curve 1


Electrical durability of contacts on resistive loading millions of operating cycles



X Current broken in A
Y Millions of operating cycles


A.C. Load Curve 2

Reduction factor k for inductive loads (applies to values taken from durability curve 1).




X Power factor on breaking ($\cos \phi$)
Y Reduction factor k

Example: An LC1-F185 contactor supplied with 115 V/50 Hz for a consumption of 55 VA or a current consumption equal to 0.1 A and $\cos \phi = 0.3$. For 0.1 A, curve 1 indicates a durability of approximately 1.5 million operating cycles. As the load is inductive, it is necessary to apply a reduction coefficient k to this number of cycles as indicated by curve 2. For $\cos \phi = 0.3$: $k = 0.6$. The electrical durability therefore becomes: 1.5×10^6 operating cycles $\times 0.6 = 900\,000$ operating cycles.



D. C. Load Limit Curve



- X Current in A
- Y Voltage in V
- 1 L/R = 20 ms
- 2 L/R with load protection diode
- 3 Resistive load

Function D : Symmetrical Flasher Relay (Starting Pulse Off)


Description

Repetitive cycle with two timing periods T of equal duration, with output(s) R changing state at the end of each timing period T.
The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

Legend

Relay de-energised

Relay energised

Output open

Output closed

C Control contact

G Gate

R Relay or solid state output

R1/ 2 timed outputs

R2

R2 inst. The second output is instantaneous if the right position is selected

T Timing period

Ta Adjustable On-delay

-

Tr Adjustable Off-delay

-

U Supply