

Product data sheet

Characteristics

2510FO1T

MANUAL STARTER 277VAC

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 86.00 USD



Main

Commercial Status	Commercialised
Product or component type	Single Unit Manual Starter
Range of product	F
Line Rated Current	16 A
Product certifications	CE CSA UL recognized
Cable entry	Without
NEMA degree of protection	Not rated (open device)
Motor power hp	1 hp 277 V AC 1 hp 230 V AC 1 hp 115 V AC
System Voltage	277 V AC
Poles description	1P
Control type	Toggle switch
Phase	1 phase
Local signalling	No indicator
Reset	Manual
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy

Ordering and shipping details

Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901735250
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------