



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1292.93 USD



Main

Commercial Status	Commercialised
Range	Thalassa
Product name	Thalassa PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLA
Enclosure nominal height	59.06 in (1500 mm)
Enclosure nominal width	39.37 in (1000 mm)
Enclosure nominal depth	16.54 in (420 mm)
Enclosure mounting	Floor-standing
Device composition	2 rear panel 2 door 2 side part 1 bottom part 1 top part

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Plain front
Number of doors	2
Door opening	Right and left 120 °
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Rear panel by fixing element Door by hinges
Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7032
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2
Product certifications	UL/CUL listed Veritas DNV Marine

Environment

IP degree of protection	IP65 completely sealed IEC 60529
IK degree of protection	IK10 plain door IEC 62262
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient air temperature for storage	-31...194 °F (-35...90 °C)

Ordering and shipping details

Category	80033 - ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	00785901127420
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	Y
Country of origin	ES

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental Profile
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------