Product data sheet Characteristics

XPSATR1153P

module XPSATR - Emergency stop and protective guard - 24V DC, time delay 3s

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 600.00 USD



Main		
Commercial Status	Commercialised	
Range of product	Preventa Safety automation	
Product or component type	Preventa safety module	
Safety module name	XPSATR	
Safety module application	For emergency stop and protective guard applications	
Function of module	Emergency stop monitoring 1-channel wiring Emergency stop monitoring 2-channel wiring Protective guard monitoring	
Safety level	Can reach SILCL 3 conforming to EN/IEC 62061 time delay safety outputs Can reach PL e/category 4 conforming to EN/ISO 13849-1 instantaneous safety outputs	
Safety reliability data	PFHd = 2E-9 1/h conforming to EN/IEC 62061 MTTFd = 85 years conforming to EN/ISO 13849-1 DC > 99 % conforming to EN/ISO 13849-1	
Type of start	Automatic Manual	
Connections - terminals	Captive screw clamp terminals, removable terminal block, clamping capacity: 2 x 0.52 x 1.5 mm² flexible cable with cable end, with bezel Captive screw clamp terminals, removable terminal block, clamping capacity: 2 x 0.22 x 1 mm² solid or flexible cable without cable end Captive screw clamp terminals, removable terminal block, clamping capacity: 1 x 0.21 x 2.5 mm² solid or flexible cable without cable end Captive screw clamp terminals, removable terminal block, clamping capacity: 2 x 0.252 x 1 mm² flexible cable with cable end, without bezel Captive screw clamp terminals, removable terminal block, clamping capacity: 1 x 0.251 x 1.5 mm² flexible cable with cable end, with bezel Captive screw clamp terminals, removable terminal block, clamping capacity: 1 x 0.251 x 2.5 mm² flexible cable with cable end, with bezel	
Output type	Relay time delay opening 3 NO, volt-free Relay instantaneous opening 3 NO, volt-free	
Number of additional	1 NC	

24 V DC (- 15...10 %)

Complementary

Synchronisation time between inputs	1 s	
Power consumption in W	2.8 W DC	
Input protection type	Internal, electronic	
Time delay range	0.13 s	
Control circuit voltage	24 V DC	
Breaking capacity	3 A at 24 V (DC-13) for relay output	
Output thermal current	6 A instantaneous and time delay outputs	

circuits

voltage

[Us] rated supply

[Ith] conventional free air thermal current	8 A	
Associated fuse rating	6 A fuse type gG for instantaneous and time delay outputs conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200	
Minimum output current	10 mA for relay output	
Minimum output voltage	17 V for relay output	
Response time on input open	<= 20 ms	
[Ui] rated insulation voltage	300 V	
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III conforming to EN/IEC 60947-5-1, DIN VDE 0110 parts 1 & 2	
Local signalling	5 LEDs	
Mounting support	35 mm symmetrical DIN rail	
Product weight	0.73 lb(US) (0.33 kg)	
Environment		
Standards	EN 60204-1 EN/IEC 60947-5-1 EN/IEC 61496-1 EN/ISO 13849-1 EN 62061 EN 50156-1	
Product certifications	CSA TÜV UL	
IP degree of protection	IP40 (enclosure) conforming to EN/IEC 60529 IP20 (terminals) conforming to EN/IEC 60529	
Ambient air temperature for operation	-13131 °F (-2555 °C)	
Ambient air temperature for storage	-13167 °F (-2575 °C)	
Ordering and shipping details		
Category	22477 - SAFETY MODULES (PREVENTA)	
Discount Schedule	SAF2	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	

Contractual warranty

Returnability

Country of origin


144 4 1 1	40 "	
Warranty period	18 months	
, , , ,		

N DE

Product data sheet Dimensions Drawings

XPSATR1153P

Dimensions



XPSATR1153P

Wiring Diagrams

Refer to the Instruction Sheet

To download the instruction sheet, follow below procedure:



XPSAC5121

- 1 Click on Download & Documents.
- 2 Click on Instruction sheet.