Product data sheet Characteristics

H266AWK SW FUSIBLE HD 600V 600A 2P NEMA12 NO KO



Product availability: Stock - Normally stocked in distribution facility

Price*: 7341.00 USD



Main

Commercial Status	Commercialised
Product or component type	Single Throw Safety Switch
Line Rated Current	600 A
Product certifications	UL listed
NEMA degree of protection	NEMA 3R/12 galvannealed steel
Device composition	None
Disconnector device type	Fusible disconnect
Short-circuit current	200 kA R, J or L 10 kA H or K
Device mounting	Surface
Number of poles	2
Electrical connection	Lugs
Series name	Heavy duty
System Voltage	600 V AC/DC
AWG gauge	AWG 3/0500 kcmil (copper or aluminium)

Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A	
Discount Schedule	DE1	
GTIN	00785901259466	
Nbr. of units in pkg.	1	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1425 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months	