

Main

Commercial Status	Commercialised
Product or component type	Starter
Range of product	S
Line Rated Current	9 A
Product certifications	CSA NEMA UL listed
Control circuit	Separate control circuit
Control type	Selector switch (HAND-OFF-AUTO)
NEMA degree of protection	NEMA 1 painted sheet steel
Rated power in HP	2 HP 575 V AC 2 HP 460 V AC 1.5 HP 230 V AC 1.5 HP 200 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	00
Control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Solid state Motor Logic class 10/20

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------