



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 534.00 USD

Main

Commercial Status	Commercialised
Range of product	8501X
Relay type	Latching
Product or component type	Relay
[In] rated current	5 A DC 10 A AC
Contacts type and composition	4 NO 4 standard contact cartridges
Poles description	4P
Control circuit voltage	12 V DC
Maximum switching voltage	250 V DC
Mounting support	Panel
Ambient air temperature for operation	-40...160 °F
Electrical connection	Screw clamp terminals
Product certifications	CE CSA UL listed
Operating time	45 ms drop-out 37 ms pick-up

Ordering and shipping details

Category	21157 - 8501 XDO (DC)
Discount Schedule	CP2
GTIN	00785901340560
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1332 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental Profile
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Warranty period	18 months
-----------------	-----------