

RM4UA33F

voltage measurement relay RM4-U - range
30..500 V - 110..130 V AC

Product availability: Stock - Normally stocked in distribution facility

Price*: 378.00 USD



Main

Commercial Status	Commercialised
Range of product	Zelio Control
Product or component type	Industrial measurement and control relays
Relay type	Voltage measurement relay
Relay name	RM4U
Relay monitored parameters	Overvoltage or undervoltage detection
Time delay type	Adjustable 0.05...30 s
Power consumption in VA	1.9...3.3 VA AC
Measurement range	50...500 V voltage DC 30...300 V voltage DC 50...500 V voltage AC 50/60 Hz 30...300 V voltage AC 50/60 Hz
Contacts type and composition	2 C/O

Complementary

[Us] rated supply voltage	110...130 V AC, 50/60 Hz +/- 5 %
Output contacts	2 C/O
Internal input resistance	1111000 Ohm 11110000 Ohm 668000 Ohm
Permissible continuous overload	400 V 550 V
Permissible non repetitive overload	550 A <= 1 s 500 A <= 1 s
Setting accuracy of the switching threshold	+/- 5 %
Switching threshold drift	<= 0.5 % within the supply voltage range (0.85...1.1 Un) <= 0.06 % per degree centigrade depending permissible ambient air temperature
Setting accuracy of time delay	10 P
Time delay drift	<= 0.5 % within the supply voltage range (0.85...1.1 Un) <= 0.07 % per degree centigrade depending on the rated operational temperature
Hysteresis	5...30 % adjustable of voltage threshold setting
Quality labels	CE
Overvoltage category	III conforming to IEC 60664-1
[Ui] rated insulation voltage	500 V conforming to IEC
Control circuit voltage limits	0.85...1.1 Uc
Supply disconnection value	> 0.1 Uc
Operating position	Any position without derating
Connections - terminals	Screw terminals 2 x 2.5 mm², flexible cable without cable end Screw terminals 2 x 1.5 mm², flexible cable with cable end
Tightening torque	5.31...9.73 lbf.in (0.6...1.1 N.m)
Mechanical durability	<= 30000000 cycles
[Ith] conventional free air thermal current	8 A

[I _e] rated operational current	0.3 A at 115 V DC-13 158 °F (70 °C) conforming to VDE 0660 0.3 A at 115 V DC-13 158 °F (70 °C) conforming to IEC 60947-5-1/1991 0.1 A at 250 V DC-13 158 °F (70 °C) conforming to VDE 0660 0.1 A at 250 V DC-13 158 °F (70 °C) conforming to IEC 60947-5-1/1991 3 A at 250 V AC-15 158 °F (70 °C) conforming to VDE 0660 3 A at 250 V AC-15 158 °F (70 °C) conforming to IEC 60947-5-1/1991 3 A at 24 V AC-15 158 °F (70 °C) conforming to VDE 0660 3 A at 24 V AC-15 158 °F (70 °C) conforming to IEC 60947-5-1/1991 3 A at 115 V AC-15 158 °F (70 °C) conforming to VDE 0660 3 A at 115 V AC-15 158 °F (70 °C) conforming to IEC 60947-5-1/1991 2 A at 24 V DC-13 158 °F (70 °C) conforming to VDE 0660 2 A at 24 V DC-13 158 °F (70 °C) conforming to IEC 60947-5-1/1991
Switching capacity in mA	10 mA at 12 V
Switching voltage	250 V AC ≤ 440 V AC
Contacts material	90/10 silver nickel contacts
Number of cables	2
Height	3.07 in (78 mm)
Width	0.89 in (22.5 mm)
Depth	3.15 in (80 mm)
Terminals description ISO n°1	(15-16-18)OC (25-26-28)OC (A1-A2)CO (C-B2-B3)CO
Output relay state	Tripped if A measured > A set
9 mm pitches	2.5
Product weight	0.37 lb(US) (0.168 kg)

Environment

Electromagnetic compatibility	Electrostatic discharge - test level 8 kV, level 3 - air discharge conforming to IEC 61000-4-2 Electrostatic discharge - test level 6 kV, level 3 - contact discharge conforming to IEC 61000-4-2
Standards	EN/IEC 60255-6
Product certifications	CSA GL UL
Directives	89/336/EEC - electromagnetic compatibility 73/23/EEC - low voltage directive
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Ambient air temperature for operation	-4...149 °F (-20...65 °C)
Relative humidity	15...85 % 3K3 conforming to IEC 60721-3-3
Vibration resistance	0.35 ms (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP50 (casing) conforming to IEC 60529 IP20(Terminals) conforming to IEC 60529
Pollution degree	3 conforming to IEC 60664-1
Dielectric test voltage	2.5 kV
Non-dissipating shock wave	4.8 kV
Resistance to electrostatic discharge	8 kV air conforming to IEC 61000-4-2 level 3 6 kV contact conforming to IEC 61000-4-2 level 3
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4 level 3
Protection against electric shocks	2 kV: level 3 conforming to IEC 61000-4-5
Disturbance radiated/conducted	CISPR 11 group 1 - class A CISPR 22 - class A

Ordering and shipping details


Category	22376 - RELAYS-MEASUREMENT(RM4)
Discount Schedule	CP2
GTIN	00785901481713
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	ID

Contractual warranty

Warranty period	18 months
-----------------	-----------


Voltage Measurement Relays

Dimensions




Voltage Measurement Relays

Rail mounting




Screw fixing



Voltage Measurement Relays


RM4UA01 and RM4UA02 Wiring Diagram



A1- Supply voltage
A2
B1, Voltages to be measured (see table below)
B2,
B3, C

Connection and current values to be measured		
RM4UA•1	B1-C	0.05...0.5 V
B2-C	0.3...3 V	
B3-C	0.5...5 V	
RM4UA•2	B1-C	1...10 V
B2-C	5...50 V	
B3-C	10...100 V	


RM4UA03 Wiring Diagram



A1- Supply voltage
A2
B2, Voltages to be measured (see table below)
B3, C

Connection and current values to be measured	
B2-C	30...300 V
B3-C	50...500 V

RM4UA31 and RM4UA32 Wiring Diagram




A1- Supply voltage
A2
B1, Voltages to be measured (see table below)
B2,
B3, C

Electrical Durability and Load Limit Curves


AC Load

Curve 1: Electrical durability of contacts on resistive load in millions of operating cycles



X Current broken in A
Y Millions of operating cycles


Curve 2: Reduction factor k for inductive loads (applies to values taken from durability Curve 1)




X Power factor on breaking ($\cos \varphi$)
Y Reduction factor K

DC Load

Load limit curve




X Current in A
Y Voltage in V
1 $L/R = 20$ ms
2 L/R with load protection diode
3 Resistive load



Function Diagram

Overvoltage Control

Function ">"



Legend

t Time delay

U A1-A2 Supply voltage

US1 Setting voltage threshold

US2 Voltage measured


15-18, 15-16; 25-28, 25-26 Output relays connections

Relay status: black color = energized.

Function Diagram

Undervoltage Control

Function "<"



Legend

t Time delay

U A1-A2 Supply voltage

US1 Setting voltage threshold

US2 Voltage measured

15-18, 15-16; 25-28, 25-26 Output relays connections

Relay status: black color = energized.