Product data sheet Characteristics

174CEV20040

ConneXium Ethernet/Modbus Plus and gateway/router

Product availability: Stock - Normally stocked in distribution facility

Price*: 7581.00 USD

Commercial Status	Commercialised
Range of product	ConneXium Ethernet gateways
Product or component type	Ethernet/Modbus Plus gateway/router
Concept	Transparent Ready
Level or class	Class B10
Communication gateway	Ethernet/Modbus Plus
Communication port protocol	Modbus Plus HDLC synchronous RS485 twisted shielded pairs cable (single or double) 1 Mbit/s Ethernet TCP/IP 10BASE-T/100BASE-TX twisted shielded pairs cable 10/100 Mbit/s
Type of connector	SUB-D 9 for connecting Modbus Plus cable RJ45 for connecting Ethernet cable
[Us] rated supply voltage	110/220 V AC
Electrical connection	1 cable twisted shielded pairs cable (single or double) < 328.08 ft (100 m) ETHERNET

Complementary

Web services	Diagnostic via predefined web pages	
Web services	Predefined web pages configuration	
	Read/Write	
Ethernet service	Modbus TCP messaging	
	SNMP agent	
Supply voltage limits	93.5242 V AC	
Supply frequency	4763 Hz	
Control type	Local/Remote control	
Local signalling	1 LED RUN	
Marking	CE	
Current consumption	1 A	
Width	4.8 in (122 mm)	
Height	9.02 in (229 mm)	
Depth	9.76 in (248 mm)	
Product weight	9.39 lb(US) (4.26 kg)	

Environment

IP degree of protection	IP20	
Product certifications	CSA 142 UL 508	
Ambient air temperature for operation	32122 °F (050 °C)	
Relative humidity	1095 % without condensation	

Ordering and shipping details

Category	18225 - PLC NTWRK HRDWR & PROWORX SOFTWARE
Discount Schedule	PC41
GTIN	00785901424802
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	N
Country of origin	TW

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 4Q2013

Contractual warranty

Warranty period	18 months
vvarianty period	TO MONUS

