Product data sheet Characteristics

P11GTV

APC Power-Saving Performance SurgeArrest, 11 Outlets with Phone and Video Protection, 120V

Purchase

Purchase P11GTV



\sim						
	W	ρІ	r٧	4	е١	۸

Model Name	APC Power-Saving Performance SurgeArrest, 11 Outlets with Phone and Video Protection, 120V
Includes	Coaxial cable,Telephone Cable,User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla,Aruba,Bahamas,Barbados,Belize,Bermuda,Brazil,Canada,Colombia,Costa Rica,Cuba,Dominican Republic,Ecuador,El Salvador,Guatemala,Haiti,Honduras,Jamaica,Madagascar,Mauritius,Mayotte,Mexico Antilles,Nicaragua,Panama,Puerto Rico,SAINT KITTS AND NEVIS,SAINT LUCIA,SAINT VINCENT AND THE GRENADINES,Trinidad And Tobago,Turks And Caicos Islands,United States,Venezuela,VIRGIN ISLANDS (UNITED STATES)

Output

Number of Outlets	11
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (manual switch)
Input Connections	NEMA 5-15P
Maximum Line Current per phase	0.0
Cord Length	1.83 meters

Surge Protection and Filtering

3400
70.0
0.0
1.0
Analog phone line for phone/fax/modem/DSL (RJ-11 connector),Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)
400

Physical

Net Weight	1.12 kg
Maximum Height	40.0 mm
Maximum Width	120.0 mm
Maximum Depth	364.0 mm
Shipping Weight	1.31 kg
Shipping Height	59.0 mm
Shipping Width	252.0 mm
Shipping Depth	428.0 mm
Master Carton Units	6.0
Master Carton Dimensions (Length x Width x Height)	16 x 11 x 18 inches
Master Carton Weight	9.25 kg
SCC Codes	1073130426923 3
Color	Black
Units per Pallet	192.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95
Operating Elevation	0-4500 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	ETL,UL 1363,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : \$150000

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

