

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	End of commercialisation
Product or component type	Starter
Range of product	S
Line Rated Current	18 A
Product certifications	CSA NEMA UL listed
Control circuit	Common control circuit
Control type	No control units
NEMA degree of protection	NEMA 1 painted sheet steel
Rated power in HP	5 HP 575 V AC 5 HP 460 V AC 3 HP 230 V AC 3 HP 200 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	0
Control circuit voltage	480 V AC 60 Hz 440 V AC 50 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Solid state Motor Logic class 20

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901070870
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------