Product data sheet Characteristics

171CCS76000

M1/M1E processor adaptor - 1 Modbus, 1 I/O bus - 20 MHz

Product availability: Stock - Normally stocked in distribution facility

Price*: 930.00 USD



Main	
Commercial Status	Commercialised
Range of product	Modicon Momentum automation platform
Product or component type	M1/M1E processor adaptor
Software designation	ProWORX 32 ProWORX NxT V2.0 Modsoft >= V2.5 Concept V2.6
Communication port protocol	Modbus
Processor name	X 86 based (INTEL, AMD)
Clock frequency	32 MHz

Complementary

Discrete I/O processor capacity	2048 I/2048 O
Memory type	RAM 256 kB Flash 256 kB
Memory description	Data 4 kB Program memory 160 kB IEC Program memory 12 kB LL984
Material	Lexan
Word length	16 bit
[Us] rated supply voltage	5.0 V DC +/-5 %
Supply	By Momentum I/O base
Exact time for 1 K instruction	1 ms
Register I/O processor capacity	4096 words total
I/O limit processor capacity	8192 bits max
I/O words/drop	80 I/O ProWORX 128 I/O Concept
Number of port	1 RS232C non isolated 1 I/O bus
Marking	CE
Product weight	0.09 lb(US) (0.042 kg)

Environment

Protective treatment	TC	
Ambient air temperature for operation	32140 °F (060 °C)	
Ambient air temperature for storage	-40185 °F (-4085 °C)	
Relative humidity	596 % without condensation	
Operating altitude	6561.68 ft (2000 m)	
Shock resistance	<= 15 gn peak (duration = 11 ms) half sine wave acceleration	
Vibration resistance	0.75 mm d.a 1 gn	
Product certifications	CUL FM Class 1 Division 2 Nema type 250 UL	

Ordering and shipping details

Category	18206 - MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	00785901308096
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 4Q2013
REACh	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
· · · · · · · · · · · · · · · · · · ·	

