

# HOM24L125TC

## LOAD CENTRE HOM MLO 240V 125A 1PH 24SP



Product availability: Stock - Normally stocked in distribution facility



### Main

Commercial Status	End of commercialisation
Product or component type	Load Centre
Range of product	Homeline
Load centre type	Main lugs
Line Rated Current	125 A
Number of spaces	2
Short-circuit current	10 kA
Number of circuits	4
Number of tandem circuit breakers	2
Phase	1 phase
System Voltage	120/240 V AC

### Complementary

AWG gauge	AWG 6...AWG 2/0 (copper) AWG 6...AWG 2/0 (aluminium)
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Provided equipment	Grounding bar ( ready assembled)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover finish	Gray baked enamel
Box number	8
Product certifications	UL listed file:E-6294

### Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901107842
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1248 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	Lifetime
-----------------	----------