Product data sheet Characteristics

8536SBG2V81AF4T

Non-Reversing Starter Size 0, 3-Pole, Thermal - Melting Alloy

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1110.00 USD

· · · · · · · · · · · · · · · · · · ·	
Commercial Status	Commercialised
Product or component type	Starter
Range of product	S
Line Rated Current	18 A
Product certifications	CSA NEMA UL listed
Control circuit	Control circuit transformer
Provided equipment	2 fuses (primary)
Control type	2 momentary push-buttons (START-STOP)
NEMA degree of protection	NEMA 1 painted sheet steel
Rated power in HP	5 HP 575 V AC 5 HP 460 V AC 3 HP 230 V AC 3 HP 200 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	0
Control circuit voltage	480 V AC 60 Hz primary circuit 120 V AC 60 Hz secondary circuit
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	00785901176503	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	MX	

Offer Sustainability

one odeamasing		
Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be Compliant on 3Q2014	_
REACh	Reference not containing SVHC above the threshold	

Contractual warranty

Contractual warranty		
Warranty period	18 months	