Product data sheet Characteristics

XAPM2203

die-cast empty control station - XAPM - Ø22 - zinc alloy - 3 horizontal openings

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 178.00 USD



Commercialised
Harmony XAP
Die-cast empty control station
XAPM
For Ø 22 mm control and signalling units
80 x 130 mm
1.93 in (49 mm)
3 cut-outs
Blue
Blue
Zinc alloy
1 hole without blanking plug for cable gland <= 0.55 in (14 mm) 1 hole with blanking plug for cable gland <= 0.55 in (14 mm)
Flush mounting
IP657 conforming to NF C 20-010 IP65 conforming to IEC 60529

Complementary

Number of vertical rows	1
Product weight	1.33 lb(US) (0.605 kg)

Environment

Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Class of protection against electric shock	Class I conforming to NF C 20-030 Class I conforming to IEC 60536	

Ordering and shipping details

22475 - WALL STATIONS	
CS2	
00785901809258	
1	
Non-Stock - Not normally stocked in distribution facility	
N	
MA	
	CS2 00785901809258 1 Non-Stock - Not normally stocked in distribution facility N


Contractual warranty

Warranty period	18 months

Product data sheet **Dimensions Drawings**

XAPM2203

Dimensions and Fixing



- 1 hole, without blanking plug, for cable gland with 14 mm/0.55 in. maximum clamping capacity
- (2) 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 14 mm/0.55 in. maximum clamping capacity
- (3) P $2 \times \emptyset$ 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- Usable depth

а		а		b		c		G H			Р	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	
80	3.15	130	5.12	51.5	2.03	50	1.97	115	4.53	49	1.93	

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions



Vertical interaxis: 30 mm/1.18 in.