



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1992.00 USD

Main

Commercial Status	Commercialised
Disconnecter device type	Fusible disconnect switch
Enclosure type	Dustproof enclosure for indoor/outdoor Ice/Sleet proof enclosure for indoor/outdoor Rainproof enclosure for indoor/outdoor
Series name	Heavy duty

Complementary

[In] rated current	100 A
AWG gauge	AWG 12...AWG 1/0 for copper cable AWG 14...AWG 1/0 for aluminium cable
Device mounting	Surface
Electrical connection	Lugs
Enclosure material	Galvannealed steel
Number of poles	3
Permissible voltage	<= 600 V
Short circuit protection	10 kA for H or K fuse 200 kA for R or J fuse
Switch function	TPST
Wiring configuration	Without neutral

Environment

Product certifications	UL listed
Contacts type and composition	1 NO/1 NC
NEMA degree of protection	NEMA 3R/12

Ordering and shipping details

Category	00160 - DE1 MISC
Discount Schedule	DE1
GTIN	00785901753865
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------