



## Main

Range of product	Zelio Relay
Product or component type	Solid state relay
Device short name	SSR
Network number of phases	1 phase
Mounting support	Panel
[In] rated current	50 A
Output voltage	24...280 V AC
Control circuit voltage	90...280 V AC

## Complementary

Contacts type and composition	1 NO
Tightening torque	<= 2.2 N.m for output <= 1.1 N.m for input
Local signalling	LED green for input status
Switching voltage	10 V AC turn-off 90 V AC turn-on
Input current limits	6 mA
Solid state output type	Zero voltage switching SCR output
Load current	0.15...50 A
Output sustained overvoltage	600 V
Surge current	625 A for 16.6 ms
Voltage drop	1.6 V on-state
Thermal resistance	0.63 °C/W
Maximum I²t for fusing	1620 A².s for 8.3 ms
Leakage current	<= 10 mA off-state
DV/Dt	500 V/µs off-state at maximum voltage
Response time	0.5 cycle turn-off 0.5 cycle turn-on

## Environment


Standards	UL E258297 CSA LR 40487 IEC 60950-1 IEC 62314
Marking	CE
IP degree of protection	IP20
Ambient air temperature for operation	-40...80 °C
Ambient air temperature for storage	-40...125 °C

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a>

Dimensions


Panel Mounting



(1)  $\varnothing 4.9 \pm 0.25 \text{ mm} / \varnothing 0.16 \pm 0.0098 \text{ in.}$  hole

## Thermal Derating Curves

### 50 A Relays



- A: Power dissipation  
B: Load current (Arms)  
C: Max. ambient temperature (°C)  
D: Base plate temperature (°C)  
(1) No heat sink

Note : These are typical curves, actual durability depends on load, environment, duty cycle, etc.