

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 26.00 USD

### Main

Commercial Status	Commercialised
Range	TeSys
Device short name	VZN
Product or component type	Additional pole
Performance level	Standard
Poles description	1P
Contacts type and composition	1 NO
Product compatibility	VN12
Network type	AC DC
Network frequency	50/60 Hz
Mounting location	Left Right

### Complementary

System Voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	12 A
[Ithe] conventional enclosed thermal current	10 A
Mechanical durability	50000 cycles
Electrical durability	50000 cycles AC-21 30000 cycles DC-1...5
Suitability for isolation	Yes
Connections - terminals	Power circuit: screw clamp terminals cable 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) - cable stiffness: solid - Power circuit: screw clamp terminals cable 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end cable end
Tightening torque	Power circuit: 6.19 lbf.in (0.7 N.m) - on screw clamp terminals
Height	1.79 in (45.5 mm)
Width	0.47 in (12 mm)
Depth	1.54 in (39 mm)
Product weight	0.04 lb(US) (0.02 kg)

### Environment

Standards	IEC 60947-3
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Shocks 11 ms 15 gn IEC 60068-2-27 Vibrations 10...150 Hz 5 gn IEC 60068-2-6
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Fire resistance	1760 °F (960 °C) conforming to IEC 60595-2-1

### Ordering and shipping details

Category	21730 - V VARIO SWITCH
Discount Schedule	CP1
GTIN	00785901303930
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	CZ

### Contractual warranty

Warranty period	18 months
-----------------	-----------