Product data sheet Characteristics

8911DPSG13V07 STARTER 600VAC 20AMP DPS +OPTIONS

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 356.00 USD

Main	
Commercial Status	Commercialised
Product or component type	Definite Purpose Starter
Line Rated Current	20 A
Motor power hp	7.5 hp 575 V AC 3 phases 7.5 hp 460 V AC 3 phases 1.5 hp 115 V AC 1 phase 7.5 hp 230 V AC 3 phases 3 hp 230 V AC 1 phase
System Voltage	600 V AC
Control circuit voltage	600 V AC 60 Hz 550 V AC 50 Hz
Phase	3 phases

Complementary

Enclosure material	Painted sheet steel	
NEMA degree of protection	NEMA 1	
Locked rotor rated current	80 A 575 V AC 100 A 460 V AC 120 A 230 V AC	
Poles description	3P	
Thermal overload type	Melting alloy	
Number of thermal units required	3	

Ordering and shipping details

Catanani	04204 0044 PD	
Category	21381 - 8911 DP	
Discount Schedule	CP1	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	CN	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant
REACh	Reference not containing SVHC above the threshold

Contractual warranty

Contracted warranty	
Warranty period	18 months