Product data sheet Characteristics

GV7AS107

TeSys GV7 - voltage release - 110...130 V AC 50/60Hz

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 96.00 USD

Range compatibility



Main			
Commercial Status	Commercialised		
Range	TeSys		
Product or component type	Shunt trip		
Device short name	GV7AS		

TeSys TeSys GV7

Complementary

Complementary		
Control circuit voltage	110130 V AC 50/60 Hz	
Control circuit voltage limits	0.71.1 Un	
[Ui] rated insulation voltage	600 V AC conforming to CSA C22.2 No 14 control circuit 690 V AC conforming to IEC 60947-1 control circuit 600 V AC conforming to UL 508 control circuit	
Threshold tripping voltage	0.20.75 Ue	
Inrush power in VA	< 10 VA AC network	
Hold-in power consumption in VA	< 5 VA AC network	
Operating time	< 50 ms conforming to IEC 60947-1	
On-load factor	100 %	
Connections - terminals	Control circuit: screw clamp terminals 1 cable 0 in² (1.5 mm²) - cable stiffness: solid Control circuit: screw clamp terminals 1 cable 0 in² (1.5 mm²) - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable 0 in² (1 mm²) - cable stiffness: flexible - with cable end	
Tightening torque	Control circuit: 10.62 lbf.in (1.2 N.m) - on screw clamp terminals	
Product weight	0.24 lb(US) (0.11 kg)	
Quantity per set	Set of 10	

Ordering and shipping details

Cracing and ompping actano			
Category	22366 - MAN STR PROTECTORS-GV1/GV3	22366 - MAN STR PROTECTORS-GV1/GV3	
Discount Schedule	l11	l11	
GTIN	00785901566946		
Nbr. of units in pkg.	1		
Product availability	Non-Stock - Not normally stocked in distribution facility		
Returnability	N	N	
Country of origin	FR	FR	

Contractual warranty

-		
Warranty period	18 months	