

# 499NEH10410

## Ethernet TCP/IP hub ConneXium - 4 ports 10BASE-T for copper

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Commercial Status	End of commercialisation
Range of product	ConneXium
Product or component type	Ethernet TCP/IP hubs
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	10BASE-T - 4 port(s) copper cable

### Complementary

Integrated connection type	Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E copper cable
Cable length	328.08 ft (100 m) copper cable
Number of hub in cascade	4
Redundancy	P1 and P2 redundant power supplies
[Us] rated supply voltage	24 V
Supply voltage limits	18...32 V DC SELV
Power consumption	4.5 W
Electrical connection	Removable connector 5 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	2 LEDs P1 P2 power supplies 1 LED per channel Ethernet link active
Alarm output	1 voltfree contact <= 1 A
Alarm function	Power supply fault Switch fault Data link status
Ethernet cabling system	TF hubs
Current consumption	80 mA 24 V DC
Width	1.57 in (40 mm)
Height	4.92 in (125 mm)
Depth	3.15 in (80 mm)
Product weight	1.17 lb(US) (0.53 kg)

## Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Relative humidity	10...95 % without condensation
IP degree of protection	IP20
Standards	CSA C22.2 No 142 CUL 60950 FM 3611 Class 1 Division 2 FM 3810 UL 1604 Class 1 Division 2 UL 508 CSA C22.2 No 213 Class I Division 2
Product certifications	GL

## Ordering and shipping details

Category	18225 - PLC NTRK HRDWR & PROWORX SOFTWARE
Discount Schedule	PC41
GTIN	00785901297390
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	DE

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0614 - <a href="#">Schneider Electric declaration of conformity</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------